

# Approval certificate

## Trade waste pre-treatment product



**Applicant:** Allied Pumps Pty Ltd  
**Postal address:** PO Box 1468 Canning Vale WA 6970

**Attention:** Terry Slack  
**Web:** [www.alliedpumps.com.au](http://www.alliedpumps.com.au)  
**Email:** [info@alliedpumps.com.au](mailto:info@alliedpumps.com.au)

**Manufacturer:** Allied Pumps Pty Ltd  
**Address:** 2 Modal Crescent, Canning Vale, WA 6155

### Product/device description

The Allied Pumps' Packaged Lint Filter Unit is designed for the removal of lint and solids prior to discharge of waste water to sewer. Lint and solids are removed by the use of A300 filter(s) supported on a frame assembly.

Units are available in a range of sizes depending upon the flow and retention required. The units are manufactured from fibreglass or concrete.


The approval certificate applies to the pre-treatment products of the following sizes:

Approval Number	Model	Max Daily Flow Rate (L)	Max Peak Flow (L/min)	Material of Construction	Chamber Size (meters)	No of A300 Filters
AN-022-03	APLF-FM2000 / 6000-2L	26,000	56	Fibreglass	1.7 Ø x 2.0-6.0 deep	2
AN-022-04	APLF-FM2000 / 6000-3L	39,000	84	Fibreglass	1.7 Ø x 2.0-6.0 deep	3
AN-022-05	APLF-FL2000 / 6000-3L	39,000	84	Fibreglass	2.2 Ø x 2.0-6.0 deep	3
AN-022-06	APLF-FL2000 / 6000-4L	52,000	112	Fibreglass	2.2 Ø x 2.0-6.0 deep	4
AN-022-07	APLF-FD1600 / 2200-1L	13,000	28	Fibreglass	1.0 Ø x 1.6-2.2 deep	1
AN-022-08	APLF-FS1500 / 3000-1L	13,000	28	Fibreglass	1.2 Ø x 1.5-3.0 deep	1
AN-022-09	APLF-FS1500 / 3000-2L	26,000	56	Fibreglass	1.2 Ø x 1.5-3.0 deep	2
AN-022-10	APLF-FG2000 / 6000-4L	52,000	112	Fibreglass	3.0 Ø x 2.0-6.0 deep	4
AN-022-11	APLF-PM2000 / 10000-2L	26,000	56	Concrete	1.8 Ø x 2.0-10.0 deep	2
AN-022-12	APLF-PM2000 / 10000-3L	39,000	84	Concrete	1.8 Ø x 2.0-10.0 deep	3
AN-022-13	APLF-PL2000 / 10000-3L	39,000	84	Concrete	2.2 Ø x 2.0-10.0 deep	3
AN-022-14	APLF-PL2000 / 10000-4L	52,000	112	Concrete	2.2 Ø x 2.0-10.0 deep	4
AN-022-15	APLF-PG2000 / 10000-4L	52,000	112	Concrete	3.2 Ø x 2.0-10.0 deep	4

### Special conditions of approval

- The product shall be *supplied* with manufacturer's installation instructions and recommended procedures for operation and maintenance.
- The product shall be *installed* and *maintained* strictly in accordance to the following Allied Pump Pty Ltd documentation:
  - Tradewaste Lint Filter System – IO&M Manual (April 2019 – version 3.0)
- This approval certificate is not a stand-alone document and **must be read** in conjunction with Water Corporation's *Typical Drawings for Trade Waste*:
  - [Commercial Laundries \(HX33-18-60\)](#)
  - [Cooling Pit / Boiler Blowdown \(HX33-18-50\)](#)
  - [Trade Waste Sampling Point \(TWSP\) \(HX33-11-30\)](#)
- The filter unit must be in place at all times as per manufacturer's instructions.**
- The temperature at the outlet of the trade waste sampling point (not the sewer connection at the property boundary) must not be more than 38° Celsius.** Water Corporation will request additional forms of pre-treatment to maintain the required temperature, if required.
- A maintenance contract is to be in place to ensure the ongoing reliability of the product.
- Water Corporation must be notified within fourteen (14) days upon installation of the product
- The use of emulsifying agents upstream of the product must not occur. Such instructions must be noted on operating documentation.

# Approval certificate



## Trade waste pre-treatment product

### Special conditions of approval (continued)

9. The product chosen must be suitably sized to avoid surge conditions.
10. Clear access for the purposes of maintenance or servicing of the pre-treatment device must be maintained at all times.
11. This approval certificate is not an endorsement of the product by Water Corporation, and no claim shall be made in advertising, promotion or other manner to the effect.
12. Water Corporation accepts no responsibility for the effective operation, performance or efficiency of the product. This approval is not an engineering approval or structural endorsement.
13. The proponent of the approved product must formally seek a request for re-approval of the product no later than three (3) months before the assigned **Validity Period** has expired from the **Date Issued** of this approval certificate.
14. Water Corporation reserves the right to vary any requirements at any time. Any application of this condition normally occurs after consultation with the manufacturer, supplier and end business user connected to Water Corporation's sewer.
15. Water Corporation shall be notified in writing if the pre-treatment device is withdrawn from sale.
16. The proponent of the approved product accepts that the information provided in this document shall be made publically available.

### General conditions of approval

Approval shall be **suspended** where any of the following conditions are not met:

1. If there is a breach of the Special Conditions.
2. The assigned **Validity Period** has expired from the **Date Issued** of this approval certificate.
3. The product shall be manufactured in accordance with Water Corporation's requirements at the time of approval.
4. The product shall be manufactured to comply according to the details noted in Tradewaste Lint Filter System – IO&M Manual (April 2019 – version 3.0), in addition to any further details provided by the proponent when seeking this approval.
5. The product supplied for use in Water Corporation's area of operations shall comply with the requirements shown on this approval certificate. Sizes, classes, lengths or other product variables which are available with the product but which are not approved as listed on this approval certificate shall not be offered by the supplier for use in Water Corporation's area of operations.
6. All discharges to sewer associated with this product must not exceed Water Corporation's *Trade Waste Acceptance Criteria*.
7. Prior to any business (which is connected to Water Corporation's sewer) installing this product the business must apply to Water Corporation for a *Trade Waste Permit* for approval to discharge.
8. If this certificate has been issued to the manufacturer of this product then it is the responsibility of the manufacturer to ensure all current and future suppliers / vendors of this product are provided a copy of this approval certificate.

Approval shall be **reviewed** where any of the following conditions occur:

1. The product is manufactured with either different materials, methods of manufacture, location of manufacture, source of raw materials, component subcontractors or models to that at the time of approval.
2. The ownership of the primary manufacturer or any subcontractors is varied from that at time of approval.
3. The standards and/or specifications to which the product was required to comply with at the time of approval have been amended or revised. It is the responsibility of the proponent to immediately advise Water Corporation of any changes to the proponent's drawings and installation, operation and maintenance manuals made at the time of approval.
4. The product has been found to sustain damage or provide unsatisfactory performance on occasions of number considered excessive by Water Corporation, when handled, stored, assembled or installed in accordance with the supplier's or manufacturer's written instructions.

<b>Approved drawing(s):</b>	Packaged Lint Filter Cooling System – General Arrangement (dated 12 February 2019)
<b>Authorising person:</b>	Stephen Jerkovic (Team Leader – Investigations)
<b>Date issued</b>	08 May 2019
<b>Validity period:</b>	Two (2) years