


# Dulux® Envirowash™

## System operating instructions

*Dulux Envirowash System*  
cleans water based  
paints and coatings from  
applicator tools. For use  
with water based paints  
and coatings only.

**Not suitable for Oil or  
Solvent based paints.**



- 1 Use water to wash tools in the unit. Fill to the Fill Line as indicated.



- 2 Remove the sink and stir vigorously for 30 seconds lifting all sediment off the bottom.
- 3 Add treatment **Additive A** as listed below.  
(NOTE: addition rate per full unit.)

Model	Part A
ES 160	50 grams
ES 800	250 grams

- 4 Stir vigorously for 1 minute.



- 5 Add treatment **Additive B** as listed below.  
(NOTE: addition rate per full unit.)


Model	Part B
ES 160	100 grams
ES 800	500 grams

- 6 Stir vigorously for 1 minute lifting all sediment off the bottom. Leave for 1 minute before re-stirring.

- 7 Leave to settle. Flocculation should start immediately.\* Settlement time is typically 2–6 hours. Best results are achieved if left to settle overnight.



- 8 Discharge cleaned water through the clean water outlet onto flat grassy areas with property owner approval, or recycle into other trade related applications.



- 9 Open sludge outlet valve and pump all sludge into sludge filter bag(s). Allow filter bag to drain, then empty out wet sludge into a suitable container for air drying.

\*If visible effects of separation are not immediate add more treatment Additive B according to dosage rate per full unit. If this still does not cause effect, see [www.dulux.com.au/trade](http://www.dulux.com.au/trade). Refer to Product Information for troubleshooting advice or call Dulux Customer Service 13 23 77.



**Envirowash™**

Dulux Australia, 1956 Dandenong Road, Clayton VIC 3168

™Dulux is a registered trademark.

™Envirowash is a trademark