

SPECIFICATIONS:-

- Material:- 304 Stainless Steel 1.6mm (bright annealed finish)
- Nominal Flow Rate:- 0.28 L/s (1000 L/h)
- Effective Flow Rate (CP11 Pump):- 0.20 L/s (720 L/h)
- Separation Process:- Enhanced Gravity
- Coalescing Medium:- Vertical Tube Packs 1 @ 290WX775Lx275H
- Weight Empty:- 4.9kg
- Weight Unfitted:- 4.1kg
- Weight Full:- 205kg
- Volume:- 156 litres (nett)
- Inlet:- DN40 BSPF
- Outlet:- DN50 BSPF
- Oil Skimmer Outlet:- DN40 BSPF
- Stand:- 25mm SHS 304 Stainless Steel
- Pump Model:- Mono CP11RJ
- Pump Suction Line:- Varies (min. DN25) Refer to Manual
- Float Switch:- MAC 3

Project

Name **CB 1.0 SS Oil/Water Separator**
General Arrangement


Drawing No. **060727PM1-01**

Revision	Drawn	Checked	Date
1	P.M.		27.07.2006

Dimensions in millimetres

General Tolerances ISO 2768-m u.n.o.

Not to Scale



1 2 3 4 5

CLEARMAKE
 water treatment & recycling solutions

CLEARMAKE PTY LTD ABN 62 125 030 364 21 PROJECT AVE NOOSA VILLE QLD 4556 AUSTRALIA
 PH: 61 7 5455 6822 FAX: 61 7 5455 6833 EMAIL: info@clearmake.com.au WEB: www.clearmake.com.au