

DrainProtector Sink Series

Installation/Maintenance Instructions for Sink units

Installation:

NOTE: It is not necessary to use silicone when installing since the unit is supplied with an effective sealing system. Use of silicone may invalidate the warranty on the DrainProtector.

- The DrainProtector is supplied in 2 sections. The **Flange** that is fitted through the sink outlet hole and the **Body**.
- Place the **Basket** and **Strainer** aside and unscrew the **Flange** from the **Body** before installing.
- Insert the DrainProtector **Flange** into the sink outlet hole ensuring that the **white gasket** provided is fitted. NB There is an O-ring seal at the top of the **Body** that will seal on the underside of the sink.
- Engage the threads of the **Flange** with the **Body** and tighten by hand taking care not to cross-thread them.
- Before fully tightening ensures the **Handle** of the valve assembly is facing in the desired direction.
- Once in the desired position use the key supplied with your DrainProtector to fully tighten the **Flange** to the **Body**. (The body can be held using a spanner or wrench on the flats provided on the valve)
- Attach the Trap and drain connection.
- Re-Fit the **Basket** and **Strainer**.
- Fill the sink with water to a depth of 25 mm and verify there are no leaks around the interfaces between the DrainProtector and the sink.
- Test the operation of the lever to ensure closing and draining operations are satisfactory.

Completion:

- Ensure the kitchen management team see and understand the operation of DrainProtector **Basket** removal and **Lever** functions.

Maintenance:

- Empty the strainer basket daily into a suitable waste bin to avoid a build up of solids or sediment reducing the draining speed.
- Never use the sink without having the basket in place.
- Wash with warm soapy water as required.