



DrainProtector™

Installation Instructions for Floor Products

Preparation:

- DrainProtectors are supplied with 150 x 150mm Grates to suit 100mm drain pipes.
- Verify that the DrainProtector floor product is the one required for the installation at hand.
- Remove the DrainProtector from the carton and retain the accompanying leaflets.
- Remove and replace the **O' Ring** fitted if other than PVC pipe is used as the drain. The smaller diameter wall **O' Ring** is used for non-PVC pipes.
- The DrainProtector is fitted during installation of the tile or vinyl sub-base to ensure correct drainage fall to the DrainProtector.

Installation:

- Apply a very light coating of lubricant to the outside of the **O' Ring**
- Insert the DrainProtector into the drain pipe to the required height.
- The upper surface of the DrainProtector will be at the same level as the tiles to be laid or
- The upper surface of the DrainProtector will be at the same level as the underside of the vinyl flooring to be installed.
- The DrainProtector will "slide" up and down inside the drain pipe to allow positioning of the upper surface at the correct height.
- Tiles or vinyl floor covering is installed in the approved manner.

Completion:

- After floor installation is complete, remove the "**protective label**" from the DrainProtector **Grate**.
- Raise the **Hinged Grate** or rotate and remove the vinyl floor **Grate**
- Remove and replace the **Basket**
- Ensure the kitchen management team see and understand the operation of DrainProtector i.e.
 - a) How to open the **Hinged Grate** or rotate and remove the **Grate** in the vinyl floor unit.
 - b) How to remove and replace the **Basket**. Ensure the **Grate** is replaced when the **Basket** is removed.
- Ensure the management team has the "**Operation, Cleaning and Maintenance Procedures**" leaflet.

